

WFS 4 CX & WFS 6 CX

WFS 4 CX and WFS 6 CX is an audio projector that complete the WFS series. They have been designed for outdoor applications. WFS 4 CX incorporates an 8" coaxial transducer and a 1.5" compression driver and WFS 6 CX a 12" woofer and the same tweeter. Their high IP rating (IP 66) makes it suitable for sports facilities, recreational areas, etc.

Both models have two connection modes (low impedance 8 Ohm and 70/100V line) allow to adjust the device for different acoustic solutions. They are available in black and White color.

TECHNICAL SPECIFICATIONS

MODEL	WFS 4 CX	WFS 6 CX
Power taps (70V)	9W/18W/37.5W/75W/150W	18.5W/37.5W/75W/150W/300W
Power Taps (100V)	18W/37.5W/75W/150W	37.5W/75W/150W/300W
Rated power (8Ω)	150W	300W
Sensitivity (1W/1m)	101dB±3dB	103dB±3dB
Frequency response	80 Hz – 18 kHz	70 Hz – 20 kHz
Woofer driver	8"	12"
Tweeter driver	1.5"	1.5"
Radiation angle	<110°	60°-120°
Enclosure material	ABS plastic	ABS plastic
Grille material	Aluminium	Aluminium
Bracket material	Stainless steel	Stainless steel
IP range	IP66	IP66
Color	Black & White	Black & White
Dimensions	390 x 370 x 330 mm	540 x 500 x 500 mm
Weight	9.1 kg	20.3 kg